Safety Data Sheet · OSHA HCS 2024

Isobutyl Alcohol 99% ACS Grade

ACS Grade · 99%

Standard	Revised	Emergency
OSHA HCS 2024 · GHS Rev. 7	2026-11-12	Chemtel 1-800-255-3924 (24/7)

1 Identification

Product Identifier	Isobutyl Alcohol 99% ACS Grade
Grade	ACS Grade
Concentration	99%
CAS Number	78-83-1
Chemical Formula	C4H10O
Molecular Weight	74.12 g/mol
Manufacturer	Alliance Chemical 204 South Edmond Street, Taylor, TX 76574
Emergency Phone	Chemtel 1-800-255-3924 (24/7)
Synonyms	Isobutanol; 2-methyl-1-propanol; 2-methylpropan-1-ol; IBA
Recommended Use	Laboratory and analytical solvent (ACS grade): chromatography, extraction and synthesis.
Restrictions on Use	For industrial and laboratory use. Causes serious eye damage: wear goggles. Flammable: keep away from ignition sources.

2 Hazard Identification



Flammable



Corrosive



Irritant / harmful

Classification

Flammable liquids, Category 3

Skin corrosion/irritation, Category 2

Serious eye damage/eye irritation, Category 1

Specific target organ toxicity, single exposure, Category 3 (respiratory tract irritation)

Specific target organ toxicity, single exposure, Category 3 (narcotic effects)

Signal Word

Danger

Hazard Statements

H226 Flammable liquid and vapor

H315 Causes skin irritation

H318 Causes serious eye damage

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

Precautionary Statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, and lighting equipment.

P242 Use non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust, fume, gas, mist, vapors or spray.

P264 Wash hands and face thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, protective clothing, and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor.

P313 Get medical advice or attention.

P321 Specific treatment (see first-aid information on this label).

P332+P313 If skin irritation occurs: Get medical advice or attention.

P362 Take off contaminated clothing and wash before reuse.

P370+P378 In case of fire: Use alcohol-resistant foam, CO2 or dry chemical powder to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents and container in accordance with local, regional, national, and international regulations.

Classification, hazard (H) and precautionary (P) statements and pictograms per OSHA HCS 2024 (29 CFR 1910.1200, Appendices A–C), aligned with GHS Rev. 7.

3 Composition / Information on Ingredients

Component	CAS No.	Formula	Concentration
Isobutyl alcohol (2-methyl-1-propanol)	78-83-1	C4H10O	≥ 99% (w/w)

Concentrations are nominal; lot-specific values appear on the Certificate of Analysis. Components not contributing to classification are omitted.

4 First-Aid Measures

Eyes Rinse with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do. Continue rinsing. Seek medical attention immediately.

Skin Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing. Wash with soap. Get medical attention immediately.

Inhalation Move person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.

Ingestion Do Not Induce Vomiting! Never give anything by mouth to an unconscious person. If conscious, wash out mouth with water. Get medical attention immediately.

Most Important Symptoms and Effects	Eye contact causes serious eye damage: pain, redness and corneal injury, which may be permanent. Skin contact causes irritation: redness, itching and pain; repeated contact may dry and crack the skin. Inhalation may irritate the nose, throat and respiratory tract (coughing, sore throat). Inhalation of vapors may cause drowsiness, dizziness, headache and nausea.
Immediate Medical Attention and Special Treatment	Immediate medical attention is required after eye contact; eye damage may continue after exposure ends.

5 Fire-Fighting Measures

Suitable Extinguishing Media	Alcohol-resistant foam, CO2, dry chemical powder. Water spray may be used to cool fire-exposed containers.
Unsuitable Extinguishing Media	Do not use a solid water stream — may scatter and spread fire.
Specific Hazards Arising from the Chemical	Vapors are heavier than air and may form explosive mixtures with air; they can travel to a source of ignition and flash back. Containers may rupture when heated.
Protective Equipment	Wear self-contained breathing apparatus and full protective clothing.
Hazardous Combustion Products	Carbon monoxide and carbon dioxide on combustion.

6 Accidental Release Measures

Personal Precautions	Use PPE as described in Section 8. Ensure adequate ventilation. Evacuate personnel to safe areas.
Hazard-Specific Precautions	Eliminate all ignition sources. Use non-sparking tools and explosion-proof equipment; ground and bond containers during cleanup.
Environmental Precautions	Prevent leakage or spillage from entering drains, sewers, or waterways.
Containment & Cleanup	Absorb with inert material. Collect in appropriate waste container. Dispose per applicable regulations.

7 Handling and Storage

Safe Handling	Use with adequate ventilation. Avoid contact with skin, eyes, and clothing. Wash thoroughly after handling. Keep container closed when not in use.
Safe Storage	Store in a cool, dry, well-ventilated area away from heat, sparks, and open flame. Keep away from incompatible materials (see Section 10). Keep containers tightly closed. Ground and bond containers when transferring material.
Specific Storage Precautions	Keep tightly closed in a cool, well-ventilated flammables area away from ignition sources and oxidizers. Store locked up. Ground and bond containers.

8 Exposure Controls / Personal Protection

Occupational Exposure Limits

Limit	Value

Limit	Value
OSHA PEL	100 ppm TWA
ACGIH TLV	50 ppm TWA
NIOSH REL	50 ppm (150 mg/m^3) TWA
IDLH	1,600 ppm

Engineering Controls	Use adequate ventilation. Provide eyewash stations and quick-drench showers accessible to areas of use.
Eye/Face Protection	Wear chemical safety goggles or face shield.
Skin Protection	Wear chemical-resistant gloves and protective clothing.
Respiratory Protection	Use a NIOSH-approved respirator with organic vapor cartridges. For confined spaces or exposures above the OEL, use supplied-air respiratory protection.

Exposure limits sourced from NIOSH Pocket Guide, OSHA 29 CFR 1910.1000 and ACGIH TLVs.

9 Physical & Chemical Properties

Appearance	Clear, colorless liquid
Odor	Alcohol-like, sweet musty odor
Odor Threshold	No data available
pH	About 7 (80 g/L aqueous solution)
Melting Point / Freezing Point	-108 °C (-162 °F)
Boiling Point	106–108 °C (223–226 °F)
Flash Point	28–31 °C (82–88 °F), closed cup
Evaporation Rate	No data available
Flammability (solid, gas)	No data available
Upper/Lower Flammability or Explosive Limits	LEL 1.7% / UEL 10.6% (v/v in air)
Vapor Pressure	7–9 mmHg (9.5–12 hPa) at 20 °C
Vapor Density	2.6 (air = 1)
Relative Density	0.80 at 20 °C (water = 1)
Solubility	Soluble in water (70–85 g/L at 20 °C); miscible with most organic solvents
Partition Coefficient (n-octanol/water)	No data available
Auto-ignition Temperature	430 °C (806 °F)
Decomposition Temperature	No data available
Viscosity	No data available
Particle Characteristics	Not applicable
Form	Liquid
Density	0.801-0.802 g/cm^3 at 20/4 °C
Refractive Index	1.397-1.399

Values shown reflect product-specific canonical data. Lot-specific ranges may vary; see the Certificate of Analysis for the shipped lot.

10 Stability and Reactivity

Reactivity	Not reactive under normal conditions of use and storage.
Chemical Stability	Stable under recommended storage conditions.
Possibility of Hazardous Reactions	None under normal processing conditions.
Conditions to Avoid	Heat, sparks, open flame, static discharge and other ignition sources.
Incompatible Materials	Strong oxidizing agents and chromium(VI) oxide; alkali and alkaline-earth metals; aluminum; rubber and some plastics.
Hazardous Decomposition Products	Carbon monoxide and carbon dioxide on combustion.

11 Toxicological Information

See below for route-specific acute toxicity data.

Likely Routes of Exposure	Inhalation, skin contact, eye contact, ingestion.
Symptoms	Eye contact causes serious eye damage: pain, redness and corneal injury, which may be permanent. Skin contact causes irritation: redness, itching and pain; repeated contact may dry and crack the skin. Inhalation may irritate the nose, throat and respiratory tract (coughing, sore throat). Inhalation of vapors may cause drowsiness, dizziness, headache and nausea.
Delayed and Chronic Effects	Repeated skin contact may cause dermatitis (dry, cracked skin).

Route	Value
LD50 Oral	2,460–3,350 mg/kg (rat)
LD50 Dermal (rabbit)	2,460–3,400 mg/kg
LC50 Inhalation	> 18 mg/L (vapor, rat, 6 h); 24.6 mg/L (4 h)

Carcinogen Classification

Agency	Status
IARC	Not listed as carcinogen.
NTP	Not listed as carcinogen.
OSHA	Not listed as carcinogen.

12 Ecological Information

Ecotoxicity	Algae ErC50: 230 mg/L (48 h, Scenedesmus subspicatus (range 230–1250 mg/L))
Persistence & Degradability	Readily biodegradable (58% ThOD in 5 d, OECD 301D)
Bioaccumulative Potential	log Kow 0.76, BCF 3 (estimated; low)
Mobility in Soil	Very high mobility in soil (estimated Koc ~2.9)

13 Disposal Considerations

Dispose of contents/container in accordance with applicable federal, state, and local regulations. Do not dispose of into drains or waterways.

EPA RCRA Waste Codes	U140 when discarded unused; F005 as a spent solvent; D001 (ignitable).

If discarded, this material may be an ignitable hazardous waste (EPA RCRA D001, 40 CFR 261.21(a)(1): flash point below 60 °C; aqueous solutions with less than 24% alcohol by volume are excluded). The waste generator must make the final hazardous-waste determination.

14 Transport Information

US DOT (49 CFR)

UN Number	UN1212
Proper Shipping Name	Isobutanol or isobutyl alcohol
Hazard Class	3
Packing Group	III
Additional US DOT Requirements	Inner packagings of 5 L or less may ship as Limited Quantity (49 CFR 173.150(c)). Not a marine pollutant.

IMDG / IATA classifications may differ from US DOT. Verify current regulations before international shipment.

15 Regulatory Information

Inventory / List	Status
California Proposition 65	Not listed
US EPA TSCA Active Inventory	Listed
EPCRA SARA 313 (TRI)	Not listed
CERCLA Reportable Quantity (RQ)	Isobutyl alcohol (CAS 78-83-1) 5,000 lb (2,270 kg), about 750 US gal; no single Alliance package reaches it. Not an EPCRA Section 313 chemical.

SARA 311/312 hazard categories correspond to the GHS classification in Section 2. Data retrieved as of: California Proposition 65 2026-11-02; US EPA TSCA Active Inventory 2026-11-02; EPCRA SARA 313 (TRI) 2026-11-02.

16 Other Information

Revision Date	2026-11-12
Format	16-section format per OSHA HCS 2024 (29 CFR 1910.1200, Appendix D), aligned with GHS Rev. 7.

Disclaimer: The information provided in this Safety Data Sheet is correct to the best of our knowledge at the date of publication. It relates only to the specific product identified and does not relate to its use in combination with other materials. ALLIANCE CHEMICAL MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ALLIANCE CHEMICAL DOES NOT ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE ARISING FROM THE HANDLING, STORAGE, USE, OR DISPOSAL OF THIS PRODUCT.

Alliance Chemical, 204 South Edmond Street, Taylor, TX 76574. Published by Alliance Chemical from first-party canonical product data. Our authority is hands-on chemical handling, DOT/GHS-compliant shipping, and government-registered distribution — not bench chemistry. This Safety Data Sheet is prepared from the regulatory data on file for this product.