

TECHNICAL DATA SHEET

Battery Water

CAS NUMBER

7732-18-5

ALLIANCE CODE

battery-water

GENERATED

2026-07-17

1. IDENTITY & COMPOSITION

PRODUCT NAME

Battery Water

ALLIANCE CODE

battery-water

GRADE

—

CONCENTRATION

—

CAS NUMBER

7732-18-5 [PubChem](#)

FORMULA

H2O [PubChem](#)

MOLECULAR WEIGHT

18.015 [PubChem](#)

PRODUCT TYPE

pure_substance

PHYSICAL & CHEMICAL PROPERTIES

One or more physical-property values are temporarily suppressed pending verification against vendor COA data. For complete properties refer to the Safety Data Sheet (SDS) or contact sales@alliancechemical.com.

FORM

Liquid [Product record](#)

ODOR

Odorless [Product record](#)

DENSITY

1 [Product record](#)

BOILING POINT

212 °F at 760 mmHg [Product record](#)

MELTING POINT

32 °F [Product record](#)

FLASH POINT

Not applicable [Product record](#)

VAPOR PRESSURE

23.75 [mmHg] [Product record](#)

SOLUBILITY (WATER)

Completely miscible [Product record](#)

REGULATORY & TRANSPORT

DOT / 49 CFR

UN NUMBER

Not regulated **Adjudicated**

HAZARD CLASS

Not regulated **Adjudicated**

PACKING GROUP

Not regulated **Adjudicated**

PROPER SHIPPING NAME

Not regulated **Adjudicated**

GHS / OSHA HAZCOM 2012

SIGNAL WORD

Not regulated **Adjudicated**

H-CODES (HAZARD STATEMENTS)

— **unknown**

P-CODES (PRECAUTIONARY STATEMENTS)

— **unknown**

OCCUPATIONAL EXPOSURE LIMITS

OSHA PEL (29 CFR 1910.1000)

— **unknown**

ACGIH TLV

— **unknown**

NIOSH REL

— **unknown**

NIOSH IDLH

— **unknown**

Transport descriptions reflect 49 CFR 172.101 lookup at time of publication. Sourced data: ECHA CLP Annex VI for harmonised classifications, NIOSH Pocket Guide for REL/IDLH, OSHA Z-Tables for PEL. Always verify against the latest regulatory text before shipment-critical decisions.

Supplier Qualification Packet

One zipped download containing the TDS, SDS, latest lot COA (when available), and a fresh Letter of Continuing Guaranty for Battery Water. Every file included is SHA-256 hashed and listed in a manifest your QA team can audit.

APPLICATION GUIDANCE

Battery Water application guidance is available on request. Contact Alliance Chemical Technical Services for grade-specific use recommendations.

STORAGE & HANDLING

RECOMMENDED STORAGE

Cool, dry, well-ventilated area in original sealed containers. Refer to product SDS for material-specific guidance.

INCOMPATIBILITIES

Consult the SDS for material-specific incompatibilities.

HANDLING PRECAUTIONS

Use standard chemical PPE — splash goggles, gloves, lab coat. Refer to SDS for hazard-specific PPE requirements.

SHELF LIFE

24 months from date of manufacture in sealed, original packaging

For full hazard, PPE, and emergency response guidance, refer to the Safety Data Sheet (SDS) for this product. The SDS controls in all cases where guidance differs.

REVISION HISTORY

Last reviewed 2026-05-20 by Hossein Taki, Vice President (Vice President, Alliance Chemical · CAGE Code 1LT50 · DOT Hazmat Registrant #2188383).

VERSION	DATE	CHANGE	TRIGGER
1.0	2026-05-20	Initial URL-first TDS published from canonical chemistry registry.	initial

This Technical Data Sheet is provided for technical reference. The Safety Data Sheet (SDS) controls in all cases where guidance differs. Values reflect Alliance Chemical canonical data at time of generation; subsequent revisions are recorded in the Revision History above.

ALLIANCE CHEMICAL

Order Battery Water

Bulk & packaged sizes · COA/SDS ships with every order