

TECHNICAL DATA SHEET

Kerosene - K1 Clean Burning Fuel

CAS NUMBER

8008-20-6

ALLIANCE CODE

kerosene-k1-clean-burning-fuel

GENERATED

2026-07-17

1. IDENTITY & COMPOSITION

PRODUCT NAME

Kerosene - K1 Clean Burning Fuel

ALLIANCE CODE

kerosene-k1-clean-burning-fuel

GRADE

—

CONCENTRATION

—

CAS NUMBER

8008-20-6 [Adjudicated](#)

FORMULA

C10H22 to C16H34 [Alliance SDS](#)

MOLECULAR WEIGHT

142.28 g/mol [Alliance SDS](#)

PRODUCT TYPE

pure_substance

PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE

Light amber liquid, transparent, low viscosity

[Product record](#)

FORM

Liquid [Product record](#)

BOILING POINT

175 [Product record](#)

MELTING POINT

-40 [Product record](#)

FLASH POINT

38 [Product record](#)

SOLUBILITY (WATER)

Low water solubility, dissolves in petroleum

[Product record](#)

REGULATORY & TRANSPORT

DOT / 49 CFR

UN NUMBER

UN1223 **Adjudicated**

PACKING GROUP

III **Adjudicated**

HAZARD CLASS

3 **Adjudicated**

PROPER SHIPPING NAME

KEROSENE **Adjudicated**

GHS / OSHA HAZCOM 2012

SIGNAL WORD

Danger **Adjudicated**

H-CODES (HAZARD STATEMENTS)

H226, H304 **Adjudicated**

P-CODES (PRECAUTIONARY STATEMENTS)

P210, P233, P280, P301+P310, P331, P370+P378,
P403+P235, P405, P501 **Adjudicated**

OCCUPATIONAL EXPOSURE LIMITS

OSHA PEL (29 CFR 1910.1000)

— **unknown**

ACGIH TLV

— **unknown**

NIOSH REL

— **unknown**

NIOSH IDLH

— **unknown**

Transport descriptions reflect 49 CFR 172.101 lookup at time of publication. Sourced data: ECHA CLP Annex VI for harmonised classifications, NIOSH Pocket Guide for REL/IDLH, OSHA Z-Tables for PEL. Always verify against the latest regulatory text before shipment-critical decisions.

Supplier Qualification Packet

One zipped download containing the TDS, SDS, latest lot COA (when available), and a fresh Letter of Continuing Guaranty for Kerosene – K1 Clean Burning Fuel. Every file included is SHA-256 hashed and listed in a manifest your QA team can audit.

APPLICATION GUIDANCE

Kerosene – K1 Clean Burning Fuel application guidance is available on request. Contact Alliance Chemical Technical Services for grade-specific use recommendations.

STORAGE & HANDLING

RECOMMENDED STORAGE

Cool, dry, well-ventilated area in original sealed containers. Refer to product SDS for material-specific guidance.

INCOMPATIBILITIES

Consult the SDS for material-specific incompatibilities.

HANDLING PRECAUTIONS

Use standard chemical PPE — splash goggles, gloves, lab coat. Refer to SDS for hazard-specific PPE requirements.

SHELF LIFE

24 months from date of manufacture in sealed, original packaging

For full hazard, PPE, and emergency response guidance, refer to the Safety Data Sheet (SDS) for this product. The SDS controls in all cases where guidance differs.

PACKAGING & LOGISTICS

SHIPPING DESCRIPTION (US DOT)

UN1223, KEROSENE, 3, PG III

Sourced from 49 CFR 172.101. Confirm against shipping documents and carrier requirements before tender.

NMFC CLASS
77.5

PLACARD
Flammable Liquid

PACKING GROUP
PG III

REVISION HISTORY

Last reviewed 2026-05-20 by Hossein Taki, Vice President (Vice President, Alliance Chemical · CAGE Code 1LT50 · DOT Hazmat Registrant #2188383).

VERSION	DATE	CHANGE	TRIGGER
1.0	2026-05-20	Initial URL—first TDS published from canonical chemistry registry.	initial

This Technical Data Sheet is provided for technical reference. The Safety Data Sheet (SDS) controls in all cases where guidance differs. Values reflect Alliance Chemical canonical data at time of generation; subsequent revisions are recorded in the Revision History above.

ALLIANCE CHEMICAL

Order Kerosene – K1 Clean Burning Fuel

Bulk & packaged sizes · COA/SDS ships with every order