

TECHNICAL DATA SHEET

Sodium Bisulfite 15% Technical Grade

Technical · 15%

CAS NUMBER

7631-90-5

ALLIANCE CODE

sodium-bisulfite-15-technical-grade

GENERATED

2026-08-31

REVISION

1.4

REVIEWED

2026-07-17 · Andre Taki

IDENTITY & COMPOSITION

PRODUCT NAME

Sodium Bisulfite 15% Technical Grade

ALLIANCE CODE

sodium-bisulfite-15-technical-grade

GRADE

Technical

CONCENTRATION

15%

CAS NUMBER

7631-90-5 [PubChem](#)

FORMULA

HNaO3S [PubChem](#)

MOLECULAR WEIGHT

104.06 [PubChem](#)

PRODUCT TYPE

solution

SPECIFICATIONS

TEST	SPECIFICATION	TYPICAL	METHOD	SOURCE
Assay (NaHSO3)	14.5 – 15.5 % by wt	15.0 %	—	Commercial practice
SO2 available	8.8 – 9.7 % by wt	9.25 %	—	Derived by dilution
Iron (Fe)	≤ 5.625 ppm	0.68 ppm	—	Derived by dilution
Sodium sulfate	≤ 1.3125 wt. %	0.32 wt. %	—	Derived by dilution

Specification values are guaranteed limits. Typical values are representative of production lots and are not guaranteed. Lot-specific certificates of analysis ship with every order.

AVAILABLE GRADES SAME CAS, ALTERNATE GRADES AND CONCENTRATIONS

GRADE	CONCENTRATION	TYPICAL ASSAY	SKU
THIS GRADE Technical	15%	—	current
ACS Grade	40%	—	sodium-bisulfite-40-acs-grade
Technical	40%	—	sodium-bisulfite-40
ACS	25%	—	sodium-bisulfite-25-acs-grade
Technical	25%	—	sodium-bisulfite-25
ACS	10%	—	sodium-bisulfite-10-acs-grade
Technical	10%	—	sodium-bisulfite-10-technical-grade
ACS	—	—	sodium-bisulfite-15-acs-grade

Typical assay shown is the rolling-window mean from the sibling product's most recent lots. Grade selection drives downstream end-use — verify the sibling grade matches your specification before substitution.

PHYSICAL & CHEMICAL PROPERTIES

PROPERTY	VALUE	SOURCE
pH	3.9 – 5.2	Interpreted
Specific Gravity (20 °C)	1.112 – 1.132	Interpreted

REGULATORY & TRANSPORT

DOT / 49 CFR

UN NUMBER

UN2693 [Adjudicated](#)

PACKING GROUP

III [Adjudicated](#)

HAZARD CLASS

8 [Adjudicated](#)

PROPER SHIPPING NAME

Bisulfites, aqueous solutions, n.o.s.

[Adjudicated](#)

GHS / OSHA HAZCOM 2012

SIGNAL WORD

Danger [Adjudicated](#)

H-CODES (HAZARD STATEMENTS)

EUH031, H302, H318 [Adjudicated](#)

P-CODES (PRECAUTIONARY STATEMENTS)

P264, P270, P301+P312, P330, P501

[Adjudicated](#)

OCCUPATIONAL EXPOSURE LIMITS

OSHA PEL (29 CFR 1910.1000)

— [no canonical](#)

ACGIH TLV

— [no canonical](#)

NIOSH REL

— [no canonical](#)

NIOSH IDLH

— [no canonical](#)

Transport descriptions reflect 49 CFR 172.101 lookup at time of publication. Sourced data: ECHA CLP Annex VI for harmonised classifications, NIOSH Pocket Guide for REL/IDLH, OSHA Z-Tables for PEL. Always verify against the latest regulatory text before shipment-critical decisions.

APPLICATIONS

Dechlorination in municipal wastewater, pulp & paper, power, and textile water treatment plants

[ineos.com](#)

Oxygen scavenger and boiler water treatment [ineos.com](#)

Preservative in the photo developer process [ineos.com](#)

Flue gas desulfurization [ineos.com](#)

Applications are drawn from published manufacturer and supplier documentation; each is sourced. Suitability for a specific use is the buyer's to confirm.

STORAGE & HANDLING

RECOMMENDED STORAGE

Cool, dry, well-ventilated area in original sealed containers. Refer to product SDS for material-specific guidance.

Class-level guidance — not product-specific; the SDS controls.

INCOMPATIBILITIES

Consult the SDS for material-specific incompatibilities.

Class-level guidance — not product-specific; the SDS controls.

For full hazard, PPE, and emergency response guidance, refer to the Safety Data Sheet (SDS) for this product. The SDS controls in all cases where guidance differs.

HANDLING PRECAUTIONS

Use standard chemical PPE — splash goggles, gloves, lab coat. Refer to SDS for hazard-specific PPE requirements.

Class-level guidance — not product-specific; the SDS controls.

SHELF LIFE

Consult Technical Services for product-specific shelf life

PACKAGING & LOGISTICS

SHIPPING DESCRIPTION (US DOT)

UN2693, Bisulfites, aqueous solutions, n.o.s., 8, PG III

Sourced from 49 CFR 172.101. Confirm against shipping documents and carrier requirements before tender.

NMFC CLASS 65	PLACARD Corrosive	PACKING GROUP PG III
------------------	----------------------	-------------------------

REVISION HISTORY

Last reviewed 2026-07-17 by Andre Taki, DOT Hazmat Specialist.

VERSION	DATE	CHANGE	TRIGGER
1.4	2026-08-19	Canonical data updated: 1 field changed via the provenance/adjudication pipeline. unNumber · canonical change (coa.data_provenance / adjudication)	canonical_change

VERSION	DATE	CHANGE	TRIGGER
1.3	2026-08-05	Canonical data updated: 3 fields changed via the provenance/adjudication pipeline. - hazardClass · canonical change (coa.data_provenance / adjudication) - packingGroup · canonical change (coa.data_provenance / adjudication) - unNumber · canonical change (coa.data_provenance / adjudication)	canonical_change
1.2	2026-07-22	Canonical data updated: 2 fields changed via the provenance/adjudication pipeline. - dotSubsidiaryHazardClass · canonical change (coa.data_provenance / adjudication) - dotProperShippingName · canonical change (coa.data_provenance / adjudication)	canonical_change
1.1	2026-07-17	Canonical data re-verified: 5 fields updated against independent vendor SDSs, CLP Annex VI, 49 CFR, and OSHA HazCom 2024 (GHS classification, hazard/precautionary codes, signal word, physical properties as applicable). - countryOfOrigin · canonical adjudication / reground (coa.data_provenance) - ghsClassification · canonical adjudication / reground (coa.data_provenance) - hazard_h_codes · canonical adjudication / reground (coa.data_provenance) - hazard_p_codes · canonical adjudication / reground (coa.data_provenance) - hsCode · canonical adjudication / reground (coa.data_provenance)	canonical_change
1.0	2026-05-20	Initial URL-first TDS published from canonical chemistry registry.	initial

This Technical Data Sheet is provided for technical reference. The Safety Data Sheet (SDS) controls in all cases where guidance differs. Values reflect Alliance Chemical canonical data at time of generation; subsequent revisions are recorded in the Revision History above.