Technical Data Sheet

Sodium Hypochlorite 1%

Technical · 1% w/w

Alliance Code	Revised	Revision
sodium-hypochlorite-1	2026-11-20	1.9

CAS number 7681-52-9	UN number UN1791	Hazard class · packing group 8 · PG III
 Structure · PubChem	Grade Technical · 1% w/w	Signal word **Warning**
Hazards Irritant / harmful H315 H319		
Proper shipping name Hypochlorite solutions		

IDENTITY & COMPOSITION

PRODUCT NAME
Sodium Hypochlorite 1%

ALLIANCE CODE
sodium-hypochlorite-1

GRADE
Technical

CONCENTRATION
1% w/w

CAS NUMBER
7681-52-9 PubChem

FORMULA
NaClO PubChem

MOLECULAR WEIGHT
74.44 PubChem

PRODUCT TYPE
Solution

SPECIFICATIONS

TEST	SPECIFICATION	TYPICAL	METHOD	SOURCE
Assay (NaOCl)	0.95 - 1.15 % w/w	—	DAC	Interpreted
Heavy Metals	max. 20 ppm	—	Ph. Eur. (2.4.8), DAC	Interpreted
Iron	max. 10 ppm	—	Ph. Eur. (2.4.9), DAC	Interpreted
Available chlorine (as Cl2)	0.90 - 1.10 % w/w	—	Iodometric titration (Na2S2O3 / starch)	Interpreted
Bromate (as is)	3.1 ppm max	—	—	Interpreted
Chlorate (as is)	286 ppm max	—	—	Interpreted
Cobalt (Co)	0.008 ppm max	—	—	Interpreted
Insolubles	0.012 wt% max	—	—	Interpreted
Copper	0.049 ppm max	—	—	Interpreted
Nickel	0.049 ppm max	—	—	Interpreted
Composition	1 % sodium hypochlorite in deionized water, by weight	—	By formulation; batch weights (scale ticket)	Interpreted

Values are reproduced from the current product reference. Source labels do not by themselves establish a supplier guarantee or a test result for your lot. Confirm applicable acceptance limits and request lot-specific documentation.

AVAILABLE GRADES SAME CAS, ALTERNATE GRADES AND CONCENTRATIONS

GRADE	CONCENTRATION	TYPICAL ASSAY	SKU
THIS GRADE Technical	1% w/w	—	current
Technical	12.5% w/w	—	sodium-hypochlorite-12-5
Technical	8.25% w/w	—	sodium-hypochlorite-8-25
Technical	6% w/w	—	sodium-hypochlorite-6
Technical	5.25% w/w	—	sodium-hypochlorite-5-25
Technical	3% w/w	—	sodium-hypochlorite-3
Technical	2% w/w	—	sodium-hypochlorite-2
Technical	10% w/w	—	sodium-hypochlorite-10

Typical assay for each grade is the average of its recent lots. Confirm a grade meets your specification before substituting it.

PHYSICAL & CHEMICAL PROPERTIES

PROPERTY	VALUE	SOURCE
Appearance	Pale yellow liquid with slight chlorine odor	Adjudicated
Color	Clear/Greenish Yellow	Interpreted
pH	10.0-12.0	Interpreted
Flash Point	Not applicable	Adjudicated
Solubility (water)	Completely miscible with water	Adjudicated

Oxidizer — decomposition rate and gas-evolution data may apply. Consult the SDS for material-of-construction guidance under shipping and storage conditions.

MATERIALS OF CONSTRUCTION SERVICE ENVELOPE ≈ 1%

MOC ratings are required for this chemical class but no compatibility data has been seeded yet. Treat as no-data and consult Alliance Technical Services before equipment selection.

REGULATORY & TRANSPORT

DOT / 49 CFR

UN NUMBER
UN1791 Adjudicated

HAZARD CLASS
8 Adjudicated

PACKING GROUP
III Adjudicated

PROPER SHIPPING NAME
Hypochlorite solutions Adjudicated

GHS / OSHA HCS 2024

SIGNAL WORD
Warning Adjudicated

H-CODES (HAZARD STATEMENTS)
H315, H319 Adjudicated

P-CODES (PRECAUTIONARY STATEMENTS)
P264, P280, P302+P352, P305+P351+P338, P321, P332+P313, P337+P313, P362, P501

Adjudicated

OCCUPATIONAL EXPOSURE LIMITS

OSHA PEL (29 CFR 1910.1000)
— no canonical

ACGIH TLV
— no canonical

NIOSH REL
— no canonical

NIOSH IDLH
— no canonical

Transport descriptions reflect 49 CFR 172.101 lookup at time of publication. Sourced data: NIOSH Pocket Guide for REL/IDLH, OSHA Z-Tables for PEL. Always verify against the latest regulatory text before shipment-critical decisions.

APPLICATION GUIDANCE

Sodium Hypochlorite 1% (Technical) is supplied for applications where controlled, selective oxidation is required. Grade selection drives the choice between bulk industrial oxidation, electronics/semiconductor cleaning, and pharmaceutical-grade disinfection.

- Pulp and textile bleaching
- Wastewater treatment and odor control
- Etching and surface cleaning (electronics-grade only)
- Disinfection and sterilization (food/pharma-grade only)
- Chemical synthesis and polymerization initiation

Materials of construction must be rated for the concentration and temperature in service. Avoid contact with reducing agents, transition metals, and organic combustibles.

STORAGE & HANDLING

RECOMMENDED STORAGE

Store out of direct sunlight in a cool area, in the original vented container. Keep away from acids, ammonia and organic materials. Strength declines with time and heat.

Adjudicated

HANDLING PRECAUTIONS

Use PPE including face shield, chemical-resistant gloves, and apron. Avoid contamination — never return unused material to the original container. Ground all transfer equipment.

Class-level guidance — not product-specific; the SDS controls.

INCOMPATIBILITIES

Acids (release toxic chlorine gas); ammonia and ammonium compounds (form chloramines); reducing agents; hydrogen peroxide; organic and combustible materials; metals such as copper, nickel, cobalt and iron (speed decomposition).

Adjudicated

SHELF LIFE

6 months from date of manufacture in sealed, original packaging

For full hazard, PPE, and emergency response guidance, refer to the Safety Data Sheet (SDS) for this product. The SDS controls in all cases where guidance differs.

PACKAGING & LOGISTICS

SHIPPING DESCRIPTION (US DOT)

```
UN1791, Hypochlorite solutions, 8, PG III
```

Sourced from 49 CFR 172.101. Confirm against shipping documents and carrier requirements before tender.

NMFC CLASS	PLACARD	PACKING GROUP
65	Corrosive	PG III

REVISION HISTORY

Last reviewed 2026-11-20 by Andre Taki, Chief Commercial Officer, DOT Hazmat–certified (49 CFR 172.704).

VERSION	DATE	CHANGE	TRIGGER
1.9	2026-11-20	Canonical data updated: 1 field changed via the provenance/adjudication pipeline. • `flashPoint` · canonical change (coa.data_provenance / adjudication)	canonical_change
1.8	2026-11-19	Canonical data updated: 1 field changed via the provenance/adjudication pipeline. • `solubility` · canonical change (coa.data_provenance / adjudication)	canonical_change

VERSION	DATE	CHANGE	TRIGGER
1.7	2026-10-13	Canonical data updated: 4 fields changed via the provenance/adjudication pipeline. • storage_precautions · canonical change (coa.data_provenance / adjudication) • incompatible_materials · canonical change (coa.data_provenance / adjudication) • conditions_to_avoid · canonical change (coa.data_provenance / adjudication) • hazardous_decomposition_products · canonical change (coa.data_provenance / adjudication)	canonical_change
1.6	2026-09-30	Canonical data updated: 1 field changed via the provenance/adjudication pipeline. • appearance · canonical change (coa.data_provenance / adjudication)	canonical_change
1.5	2026-08-12	Canonical data updated: 1 field changed via the provenance/adjudication pipeline. • unNumber · canonical change (coa.data_provenance / adjudication)	canonical_change
1.4	2026-08-05	Canonical data updated: 2 fields changed via the provenance/adjudication pipeline. • hazardClass · canonical change (coa.data_provenance / adjudication) • unNumber · canonical change (coa.data_provenance / adjudication)	canonical_change
1.3	2026-07-22	Canonical data updated: 5 fields changed via the provenance/adjudication pipeline. • ghsClassification · canonical change (coa.data_provenance / adjudication) • hazard_h_codes · canonical change (coa.data_provenance / adjudication) • hazard_p_codes · canonical change (coa.data_provenance / adjudication) • dotSubsidiaryHazardClass · canonical change (coa.data_provenance / adjudication) • packingGroup · canonical change (coa.data_provenance / adjudication)	canonical_change
1.2	2026-07-17	Canonical data updated: 1 field changed via the provenance/adjudication pipeline. • dotProperShippingName · canonical change (coa.data_provenance / adjudication)	canonical_change

VERSION	DATE	CHANGE	TRIGGER
1.1	2026-07-17	Canonical data re-verified: 7 fields updated against independent vendor SDSs, CLP Annex VI, 49 CFR, and OSHA HazCom 2024 (GHS classification, hazard/precautionary codes, signal word, physical properties as applicable). • countryOfOrigin · canonical adjudication / reground (coa.data_provenance) • ghsClassification · canonical adjudication / reground (coa.data_provenance) • hazard_h_codes · canonical adjudication / reground (coa.data_provenance) • hazard_p_codes · canonical adjudication / reground (coa.data_provenance) • hsCode · canonical adjudication / reground (coa.data_provenance) • packingGroup · canonical adjudication / reground (coa.data_provenance) • signalWord · canonical adjudication / reground (coa.data_provenance)	canonical_change
1.0	2026-05-20	Initial URL-first TDS published from canonical chemistry registry.	initial

This Technical Data Sheet is provided for technical reference. The Safety Data Sheet (SDS) controls in all cases where guidance differs. Values reflect Alliance Chemical canonical data at time of generation; subsequent revisions are recorded in the Revision History above.