

TECHNICAL DATA SHEET

VM&P Naphtha

CAS NUMBER	ALLIANCE CODE	GENERATED
64742-89-8	vm-p-naphtha	2026-07-17

1. IDENTITY & COMPOSITION

PRODUCT NAME	ALLIANCE CODE
VM&P Naphtha	vm-p-naphtha
GRADE	CONCENTRATION
—	—
CAS NUMBER	FORMULA
64742-89-8 Adjudicated	C5-C11 Hydrocarbons Alliance SDS
MOLECULAR WEIGHT	PRODUCT TYPE
120 g/mol Alliance SDS	pure_substance

PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE	FORM
Clear, colorless liquid Product record	Liquid Product record
SPECIFIC GRAVITY (20 °C)	BOILING POINT
0.7385 g/mL Vendor COA	146°C Product record
MELTING POINT	FLASH POINT
-60°C Product record	4°C Product record
SOLUBILITY (WATER)	REFRACTIVE INDEX (ND 20)
Insoluble in water, soluble in organic solvents Product record	1.4081 Vendor COA

MATERIALS OF CONSTRUCTION

MATERIAL	RATING	MAX T (°C)	NOTES	SOURCE
Buna-N (NBR) Elastomer	Good	80	Good for non-aromatic hydrocarbons; poor for aromatics.	Parker O-ring Chemical Compatibility
EPDM Elastomer	Not recommended	—	Swells in hydrocarbons; never use.	Parker O-ring Chemical Compatibility
Viton (FKM) Elastomer	Excellent	100	Standard for hydrocarbon service.	Parker O-ring Chemical Compatibility
PTFE Fluoropolymer	Excellent	200	Universal.	Cole-Parmer Chemical Compatibility
316L Stainless Steel Metal	Excellent	100	Inert.	Cole-Parmer Chemical Compatibility
Carbon Steel Metal	Good	80	Acceptable for dry hydrocarbons.	Cole-Parmer Chemical Compatibility
HDPE Thermoplastic	Not recommended	—	Aromatic solvents swell and dissolve HDPE.	Cole-Parmer Chemical Compatibility

Ratings reflect the service envelope (concentration × temperature) shown. Always confirm against your specific duty cycle and contact-time before equipment selection. The most cautious rating across overlapping references is shown.

REGULATORY & TRANSPORT

DOT / 49 CFR

UN NUMBER

UN1268 **Vendor Label**

PACKING GROUP

II **Adjudicated**

HAZARD CLASS

3 **Adjudicated**

PROPER SHIPPING NAME

Petroleum distillates, n.o.s. (VM&P naphtha)
Adjudicated

GHS / OSHA HAZCOM 2012

SIGNAL WORD

Warning **Adjudicated**

H-CODES (HAZARD STATEMENTS)

H226 **Adjudicated**

P-CODES (PRECAUTIONARY STATEMENTS)

P210, P233, P280 **Adjudicated**

OCCUPATIONAL EXPOSURE LIMITS

OSHA PEL (29 CFR 1910.1000)

— **unknown**

ACGIH TLV

— **unknown**

NIOSH REL

— **unknown**

NIOSH IDLH

— **unknown**

Transport descriptions reflect 49 CFR 172.101 lookup at time of publication. Sourced data: ECHA CLP Annex VI for harmonised classifications, NIOSH Pocket Guide for REL/IDLH, OSHA Z-Tables for PEL. Always verify against the latest regulatory text before shipment-critical decisions.

Supplier Qualification Packet

One zipped download containing the TDS, SDS, latest lot COA (when available), and a fresh Letter of Continuing Guaranty for VM&P Naphtha. Every file included is SHA-256 hashed and listed in a manifest your QA team can audit.

APPLICATION GUIDANCE

VM&P Naphtha is a nonpolar solvent used for hydrocarbon extraction, coatings, and degreasing.

- Coatings, paints, and adhesives
- Industrial degreasing
- Hydrocarbon extraction and recovery
- Rubber and polymer processing
- Cleaning of oil-based residues

Highly flammable and electrostatic-prone. Use grounded transfer equipment and inert gas blanketing where appropriate.

STORAGE & HANDLING

RECOMMENDED STORAGE

Cool, well-ventilated flammable-liquid storage. Tightly sealed containers. Segregate from oxidizers. Bond and ground bulk storage;...

INCOMPATIBILITIES

Strong oxidizers, halogens, nitric acid. Some grades react with rubber and certain plastics — verify gasket and hose compatibility.

HANDLING PRECAUTIONS

Eliminate ignition sources. Use chemical-resistant nitrile or PVA gloves. Bond and ground all transfer equipment. Vapors heavier than air ...

SHELF LIFE

24 months from date of manufacture in sealed, original packaging

For full hazard, PPE, and emergency response guidance, refer to the Safety Data Sheet (SDS) for this product. The SDS controls in all cases where guidance differs.

PACKAGING & LOGISTICS

SHIPPING DESCRIPTION (US DOT)

UN1268, Petroleum distillates, n.o.s. (VM&P naphtha), 3, PG II

Sourced from 49 CFR 172.101. Confirm against shipping documents and carrier requirements before tender.

NMFC CLASS 70	PLACARD Flammable Liquid	PACKING GROUP PG II
------------------	-----------------------------	------------------------

REVISION HISTORY

Last reviewed 2026-05-20 by Hossein Taki, Vice President (Vice President, Alliance Chemical · CAGE Code 1LT50 · DOT Hazmat Registrant #2188383).

VERSION	DATE	CHANGE	TRIGGER
1.0	2026-05-20	Initial URL-first TDS published from canonical chemistry registry.	initial

This Technical Data Sheet is provided for technical reference. The Safety Data Sheet (SDS) controls in all cases where guidance differs. Values reflect Alliance Chemical canonical data at time of generation; subsequent revisions are recorded in the Revision History above.

ALLIANCE CHEMICAL

Order VM&P Naphtha

Bulk & packaged sizes · COA/SDS ships with every order